Tel: 612 9979 8777

Pan Tilt Pushrod Inspection Camera System



Features

- * 360-degree rotation camera head, Pan 360 $^{\circ}\,$, Tilt 180 $^{\circ}\,$
- * 1/3 CMOS,1.3MP pixel AHD camera head, waterproof up to 10 bars.
- * 10 inch IPS LCD screen, 1280*720 resolution
- * DVR control box with audio, video, recording and photography function.
- * 60m / 100m / 150m Dia.9mm fiberglass copper axis cable, it can make good camera image for long cable
- * USB Bluetooth keyboard to typewrite the words
- * Camera video resolution is 720p
- * Built in 8800mA lithium battery inside, support unit working more than 6 hours
- * Digital meter counter function, error is less than 1%

Camera Parameter Table



- * Camera size 50mm x 154mm, sensor 1/3" CMOS,1.3MP pixel
- * Built-in 512Hz transmitter optional
- * Waterproof IP68 up to 10 bars
- * View range 120°
- * Rotation: Pan 360°, Tilt 180°
- * Lens position automatic reset
- * Slip coupling for rotation axle
- * 6pcs high light LED lighting adjustable
- * Detachable with pins type connection to Cable Reel
- Camera Head * Lens window sapphire glass

ENDETEK Australia P/L Address: Unit 8 / 2 Apollo Street, Warriewood NSW 2102 Sydney AUSTRALIA www.endetek.com.au sales@endetek.com.au



and the same of th	* 10"HD IPS LCD Screen, 1280X720 resolution, 16:9 display model * PT camera Joystick
	* AHD DVR SYSTEM with recording 720P video
	* DVR recording system with AVI video format
	<u> </u>
0	* USB Bluetooth Keyboard real time typewriting
	* USB port to connect storage device (16G USB flash disk)
	* Built-in 8800mA rechargeable lithium battery pack
·/·	* Battery level indicator
H E	* Sunshade is included
	* Box size 42x33x15cm
	* AC 110V-240V 1.5A power charger
ADH DVR Control Unit	* Charging time 8 hours, working time about 5 hours
	* Fibergless much red cable
	* Fiberglass push rod cable
4 7 3	* Cable diameter 9mm
	* Cable length 60m to 150m optional
	* Reel size L70*W28*H84cm
	* Reel brake available
	* Updated digital meter counter, error rate less than 1%
Cable Reel	
~ ~ 00	
	* Plastic & nylon
	* Dia. 85mm
O	* Dia.220mm
Standard Skid	
	* Stainless steel & nylon
	* Size adjustable
	* Min Dia 280mm
	Max Dia.450mm (Optional,)
	(Optional,)
Stainless Steel Roller Skid	
	1. Pan tilt rotation camera head
	2. 60m 9mm cable reel
	3. DVR control box with remote controller
Packing List	4. 5pin Link cable (3m /5m)
	5. Test Cable for Pan tilt camera head
	6. Charger adapter 7. 16G USD flash disk
	8. Seal ring 2pcs
	9. Earphone
	10. Camera skid (Dia.85mm and Dia.220mm)
	11. User manual

ENDETEK Australia P/L Address: Unit 8 / 2 Apollo Street, Warriewood NSW 2102 Sydney AUSTRALIA

www.endetek.com.au sales@endetek.com.au



AHD DVR Control Unit Operate Control Button Function

Video Switch Knob	CAM 1: Φ16mm/Φ23mm/Φ29mm Camera head 4 core Signal input
	CAM 2: Pan/tilt camera head 5 core Signal input
	Video for BNC or RCA video input
On/Off Switch Knob	Charge: indicating charging status
	OFF: Turn off the control kit power
	ON: Turn on the control kit power
Battery/Charge Button	Switch battery/charge
Camera LED Dimmer	Adjustable camera LED brightness
Microphone Operation	Press down the button, the microphone is working
PT Joystick Control	Control camera Pan Tilt rotation
Keyboard	USB Bluetooth keyboard
USB Port	Connect with USB flash Disk
Terms & Conditions:	

Terms & Conditions:

Package info 1pcs/ctn

G. W=68KG + 10KG

Carton box size: 83x41x90.5cm 49X22X43cm