



ENDETEK

A U S T R A L I A

ENDETEK

EDT-PP240



Two accessory USB Charging Sockets rated at 2.1Amps each, power button for USB ports and safety fuse.

The Powersafe RCD DUO offers a much broader range of protection by operating in various earthing environments. The RCD DUO is designed to isolate power in the occurrence of a fault to earth on multiple earthed neutral (MEN) and IT type systems. Earth Fault Protection on IT, TT & MEN type systems



240V Output @ 500w



Transport Case Dimensions

- External Dimensions: 265 x 240 x 175 mm
- Internal Dimensions:
- Top of the Case: 235 x 180mm
- Base of the Case: 235 x 180mm
- Depth of Base: 120mm
- Depth of Lid: 30mm
- Meet TSA airline Safe Requirements
- System Weight 3.6 Kg

AC - Inverter

Power:	500W
Surge Power:	1500W
Output Waveform:	Modified sine wave (THD<3%)
Output Frequency:	50Hz±0.1%
AC Output Voltage:	240VAC
Voltage Range:	10V-15V
Low Voltage Alarm:	10.5V± 0.5V
Converting Max Efficiency.	90% (Full Loading)/95% (1/3 Loading)
No Load Consumption:	< 0.7A
DC - USB Battery & Charger	
Voltage:	12.8V Nominal
Capacity:	7Ah or 8.96-Watt hour
Runtime:	4 Hours @ 25% Duty Cycle Max
Charge Time:	2-3 Hours with supplied 4A (LiFePo ₄) Charger
USB Output:	Dual 5VDC @2.1A Max each
Battery Type:	Lithium Ferrous Phosphate (LiFePo ₄)

Contact details below for more information or to place an order:

ENDETEK Australia Pty Ltd

8/2 Apollo St, Warriewood NSW 2102

Ph: 02 9979 8777 or email us: sales@endetek.com.au