

Tel: 612 9982 3227

## **Pan Tilt Pushrod Inspection Camera System**



## **Features**

- \* 360-degree rotation camera head, Pan 360 $^{\circ}\,$  , Tilt 180 $^{\circ}\,$
- \* 1/3 CMOS,1.3MP pixel AHD camera head, waterproof up to 10 bars.
- \* 8-inch IPS LCD screen, 1280\*720 resolution
- \* Options of 60m / 100m / 150m Dia.9mm fiberglass copper axis cable
- \* USB Bluetooth keyboard to typewrite the words
- \* Camera video resolution is 720p
- \* Built in 7000mA lithium battery inside, support unit working more than 6 hours
- \* Digital meter counter function, error is less than 1%

## Camera Parameter Table



- \* Camera size 50mm x 154mm, sensor 1/3" CMOS, 1.3MP pixel
- \* Built-in 512Hz transmitter optional
- \* Waterproof IP68 up to 10 bars
- \* View range 120°
- \* Rotation: Pan 360°, Tilt 180°
- \* Lens position automatic reset
- \* 6pcs high light LED lighting adjustable
- \* Detachable connection to Cable Reel
- \* Stainless steel LED cover, anti-scratch
- \* Camera skids: 2 kinds different size skids (Dia.85mm/Dia.150mm)
- \* Camera housing stainless steel and Aluminum
- \* Slip coupling for rotation axle
- **Camera Head** \* Lens window sapphire glass

ENDETEK Australia P/L Address: Unit 8 / 2 Apollo Street, Warriewood NSW 2102 Sydney AUSTRALIA www.endetek.com.au sales@endetek.com.au

Professional Pushrod Camera Tel: 612 9982 3227

	* 8"HD IPS LCD Screen, 1280X720 resolution, 16:9 display model
	* HD DVR SYSTEM with recording 720P video
300 SB 00 8	* DVR recording system with AVI video format
	* Waterproof LCD panel
	* USB wireless Keyboard real time typewriting
	* USB port to connect storage device (16G USB flash disk)
	* Built-in 7000mA rechargeable Li-ion Battery Pack
	* Battery level indicator
	* Sunshade is included
	* Box size 23x20x5cm
	* AC 110V-240V 1.5A power charger
	* Charging time 7 hours, working time about 4 hours
Multiple DVR Control Unit	* Can fix on the cable reel, can be handhold, can hang on the neck(optional)
	* Fiberglass push rod cable
	* Cable diameter 9mm
	* Cable length 60m to 150m optional
	* Reel size L70*W28*H84cm
	* Reel brake available
	* Updated digital meter counter, error rate less than 1%
Cable Reel	opuated digital meter counter, error rate less than 170
00	
	* Plastic & Nylon
	* Dia. 85mm
	* Dia. 220mm
Chan doud Child	Did.22011111
Standard Skid	
	* Stainless steel & nylon
	* Size adjustable * Min Dia 280mm
	Max Dia.450mm
	(Optional, USD80)
Stainless Steel Roller Skid	
	* Size: 32x22x25cm
	* Easy to carry
	* Include:
NATIONAL PROPERTY.	Camera head
	Control unit Wireless keyboard
	Test cable
	Link cables
Carrying Bag	User manual
Terms & Conditions:	
Package info	1pcs/ctn
	G. W=68KG + 8KG
L	

ENDETEK Australia P/L Address: Unit 8 / 2 Apollo Street, Warriewood NSW 2102 Sydney AUSTRALIA www.endetek.com.au sales@endetek.com.au



Professional Pushrod Camera Tel: 612 9982 3227

Carton box size: 84.5x43.5x93cm 40X30X30cm

ENDETEK Australia P/L Address: Unit 8 / 2 Apollo Street, Warriewood NSW 2102 Sydney AUSTRALIA www.endetek.com.au sales@endetek.com.au